

	66M	66MKS plus warm water & cook	66MW hangmodel	66MK cook	66MV warm water only	62M	62MS plus warm water	64M	60M	61MS plus warm water	67MS plus warm water	67MV warm water only	71M	71MS plus warm water	70M	REFO	2000K	2000KV plus warm water
Specifications																		
Capacity kW air heating	1,6	0,8	1,6	1,6		2,4	0,8	5,8	5,8	1,9	2,3		1,6	1,2	1,6	7,0	4,2	1,5
Capacity kW radiator heating		0,8			1,6		1,6			4,0	4,9	8,1		0,5				2,7
Capacity kcal. air heating	1400	700	1400	1400		2100	700	5000	5000	1600	2000		1400	1000	1400	6000	3620	1293
Capacity kcal. radiator heating		700			1400		1400			3400	4200	7000		400				2327
Advised room volume m3	14	14	14	14	14	21	21	50	50	50	62	70	14	14	14	60	40	40
Advised room volume m3 insulated	23	23	23	23	23	35	35	83	83	83	103	117	23	23	23	100	70	70
Height, cm	42	45	37	45	55	44	44	63	62	71,5	90	76	25	25	34,5	81	59	59
Diameter, cm	16,5	16,5	NA	16,5	24	26	26	32	32	32	36,5	NA	NA	NA	NA	NA	26	26
Width, cm	round	round	17	round	round	round	round	round	round	round	round	40	25	25	32,5	39	round	round
Depth, cm	round	round	28	round	round	round	round	round	round	round	round	40	25	25	49,5	32	round	round
Weight in kgs	4	7	6	4,5	8	7	8	10	10	14	18	30	8,5	9	18	48	10	11,5
Chimney diameter, mm	70	70	70	70	70	90	90	90	90	90	114	114	70	70	70	120	90	90
Ventilation from floor, mm	420	345	370	345	490	345	345	525	420	525	760	715	205	205	345	710	425	425
Fuel consumption, min. litre/hour	0,12	0,12	0,12	0,12	0,12	0,12	0,12	0,18	0,18	0,18	0,3	0,3	0,12	0,12	0,12	0,2	0,18	0,18
Fuel consumption, max. litre/hour	0,3	0,3	0,3	0,3	0,36	0,36	0,36	0,8	0,8	0,8	1	1,5	0,3	0,3	0,36	0,9	0,54	0,54